



Firma: PB Nitom d.o.o.
Adresa: Gruje A.Kostadinović 15A
Telefon: 018/41 51 501
Fax:
PIB: 100334173
E-mail: webprodaja@nitom.rs

Tenda MW3 AC1200 dual band distribution mesh WiFi system 200m2 2PACKS

Šifra: 58619
Kategorija proizvoda: Ruteri i Acces point
Proizvođač: Tenda

Cena: **8.080** rsd



MW3 is a 1200Mbps dual band distribution mesh WiFi system designed for 100-300? houses, bringing you with whole home WiFi coverage, as well as fast and stable internet connection. Pack of 3 provides you with up to 300? WiFi range; while pack of 2 provides you with up to 200? WiFi range. Compliant with IEEE 802.11v and IEEE 802.11r seamless roaming protocols, MW3 supports automatic network optimization and automatic routing selection, allowing you to enjoy more stable and flexible wireless network. Standard Protocol: IEEE802.3, IEEE802.3u Interface: 2 Ethernet ports per mesh node WAN and LAN on primary mesh node Both act as LAN ports on additional mesh nodes Antenna: 2*3dBi internal dual band antennas Button: 1 reset button Power: Input:100-240V—50/60Hz Dimension: 90 x 90 x 90mm Wireless Standards: IEEE 802.11ac/a/n 5GHz IEEE 802.11b/g/n 2.4GHz Wireless Frequency2.4G: 2400MHz-2483MHz 5G: 5150MHz-5250MHz or 5725MHz-5825MHz Data Rate: 5GHz: Up to 867Mbps 2.4GHz: Up to 300Mbps Frequency: Simultaneous dual band 2.4GHz 5GHz Basic Features:SSID Broadcast Beamforming Wireless Security: Mixed WPA/WPA2-PSK(default) Wireless roaming: Comply with IEEE802.11v/r Internet Connection Type: PPPoE, Dynamic IP, Static IP, Bridge Mode DHCP ServerDHCP Server DHCP Client List Virtual Server: Port Forwarding UPnP QoS: Support Smart QoS Firewall: Forbid UDP flood attack Forbid TCP flood attack Forbid ICMP flood attack DNS: Support manually setting DNS server VPN: IPsec pass through PPTP pass through L2TP pass through Other: Parental Control Guest Network Firmware upgrade online Reset to factory settings Setup Requirements: A mobile device running Android 4.0+ or iOS 8+ Temperature: Operating Temperature: 0? ~ 40? Storage Temperature: -40? ~ 70?. Humidity: Operating Humidity:10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing. Certification: FCC, CE, RoHS, EAC, IC Package Content: (2-pack) 2 identical mesh nodes 2 power adapters Quick install guide 1 ethernet cable